


## Technical Information

The Predator ES1290T3 is an Absorbent Glass Mat (AGM) battery with T3 terminals designed for general purpose & standby applications including UPS, communication & security systems. Their ActivFire certification makes them an excellent choice for fire panel applications.

The lead calcium tin grids produce less gassing and a low self discharge rate. The Predator ES series are manufactured in a facility which is ISO 9001, 14001 & 45001 certified.

The valve regulated, non-spillable design delivers outstanding cycle life and a low self discharge rate for longer shelf life.

For deep cycle applications, the Predator ED series are recommended.




## Features & Benefits



- ActivFire Certified
- Heavy Duty, Non-Spillable Design
- Glass Mat Separator Construction
- High Energy Density & Cycle Life
- Low Self Discharge
- 5 years design life (@25°C)

## Float Service Life @ 25°C



## Technical Specifications

<b>Battery Type</b>	General Purpose AGM	<b>Case Material Colour</b>	ABS Blue Case, White Lid
<b>Voltage</b>	12V	<b>Charge Current</b>	Recommended: 0.9A Maximum: 2.7A
<b>Capacity (20 / 10 / 5 / 3Hr)</b>	9 / 8.1 / 7.55 / 5.61Ah	<b>Charge Voltage</b>	14.4 – 15.0V @25°C (Temp. Coeff. -30mV/°C)
<b>Internal Resistance (25°C)</b>	Approx. 17.0mΩ	<b>Float Voltage</b>	13.5 – 13.8V @25°C (Temp. Coeff. -20mV/°C)
<b>Overall Size (LxWxH ±2mm)</b>	151 x 65 x 105mm	<b>Operating Temp. Charge</b>	-20 to 40°C
<b>Nominal Weight</b>	2.53kg	<b>Operating Temp. Discharge</b>	-15 to 50°C